

28SVRT

BREAKER
SPECIFICATION
SHEET



MACDONALD

28SVRT

This Macdonald vibration reduced breaker will suit most medium to heavy breaking jobs on concrete, asphalt & footpaths.

Designed to withstand the demands of the plant hire industry, combined with an excellent power to weight ratio.

The 28SVRT strikes a balance between hard hitting performance & vibration reduced levels required by today's operators.

BENEFITS

- Ergonomic handles to reduce operator exposure to hand arm vibration.
- Cushioned grips for operator comfort & productivity.
- Silencer for effective noise suppression.
- Well balanced, manoeuvrable & high strike energy.
- Quick change retainer.
- Easily maintained without specialist tools.
- Drop forged components for minimum wear & maximum life.
- Built in reservoir for automatic oiling & smooth continuous operation.
- Small number of moving parts to minimise internal wear.



SPECIFICATION

WEIGHT	28.5 KGS	AIR CONSUMPTION	54 CFM	
VIBRATION	4.6 MS ²	NOISE LEVEL	108 DB(A)	
FREQUENCY	960 BPM	LENGTH	712 MM	
CHUCK SIZE	WORKING PRESSURE	BORE	STROKE	AIR HOSE
32 or 28 MM	6 BAR 90 PSI	44 MM	170 MM	19 MM

For sales & enquiries call:
+44 (0) 1355 221215



Macdonald Air Products Ltd. Registration in Scotland No.366829

77 Carron Place, Kelvin Industrial Estate, East Kilbride, G75 0YL, Scotland
Email: info@macdonaldairtools.com | Web: macdonaldairtools.com